A Pigment of Your Imagination



TECHNICAL DATA SHEET

Date: 01.01.2023 Revision: 04

| Product Description | | | | | |
|--|-----------------------|-------------------|----------------------------|--|--|
| C.I Generic Name | MIDDLE CHROME (PY 34) | NPPL Product Code | Navfast Middle Chrome 7002 | | |
| C.I No. | 77600-77603 | CAS No. | 1344-37-2 | | |
| EINECS No. | 215-693-7 | Chemical Type | Chrome Yellow | | |
| Molecular Formula | PbCrO4+PbSO4 | Molecular Weight | 576.07 | | |
| Chemical Name: Lead sulfochromate vellow | | | | | |

| Physical Properties | |
|--|---------|
| Residue on 325 mesh sieve % by mass max. | 0.5 |
| Oil Absorption | 20 - 40 |
| Salt Content (%) Max. | 1 |
| Moisture Content (%) Max. | 1 |
| Conductivity µS/CM (max) | 500 |
| Relative density | 5.4 |

| Tint Tone: 1:10 Ratio |
|-----------------------|
| |
| |
| |
| |
| |
| |

| Fastness properties | | | |
|---------------------|-----------|----------------------|--|
| Heat °C | | 200-220 °C / 30 min. | |
| Light | Mass Tone | 7 | |
| Light | Tint Tone | 6 | |
| Weather | Mass Tone | 5 | |
| Weather | Tint Tone | | |
| Overspray | | 5 | |

| Solvent Fastness properties | | |
|-----------------------------|---|--|
| Water | 5 | |
| Ethanol | 5 | |
| Ethyl Acetate | 5 | |
| MEK | 5 | |
| Acid | 5 | |
| Alkali | 5 | |

| Application | | |
|----------------------|---|--|
| PP / HDPE / LDPE | • | |
| Engineering Polymers | • | |
| PVC | • | |
| Rubber / Fiber | • | |

| Specification | | | | |
|------------------------------|------------------------|--|--|--|
| Coloristic properties - Tint | Strength: ±5% | | | |
| Coloristic properties - Tint | DA,DB,DE,DC,DH,DL: ±1 | | | |
| Light fastness: Scale 1-8 | 1~Poor & 8 ~ Excellent | | | |
| Weather fastness : Scale 1-5 | 1~Poor & 5 ~ Excellent | | | |
| Overspray: Scale 1-5 | 1~Poor & 5 ~ Excellent | | | |
| Solvent Fastness: Scale 1-5 | 1~Poor & 5 ~ Excellent | | | |

Note: The colors above have been generated electronically and should therefore not be used for comparison purposes. The colors are meant to give a first impression of the colorant shade.

The data contained in this publication are based on our current knowledge and experience. In view of the many factors that may affect processing and application of our Product, these data do not relieve processors from carrying out their own investigations and tests; neither do these data imply any guarantee of certain properties, nor the suitability of theproduct for a specific purpose. Any descriptions, drawings, photographs, data, proportions, weights, etc. given herein may change without prior information and do not constitute the agreedcontractual quality of the product. It is the responsibility of the recipient of our products to ensure that any proprietary rights and existing laws and legislation are observed.











CIN No: U24220GJ1998PTC033736

NAVPAD PIGMENTS PVT. LTD.

A Govt. Of India Recognized Star Export House

Regd. Office & Factory: 1196/1/A & B, Ghumasan Patia Road, Chhatral - Mehsana Highway, Rajpur - 382715, Gujarat, India

T: +91-982-503-1388 / +91-2764-278338

E: exports@navpadpigments.com W: www.navpadpigments.com